

Power Schottky rectifier

Main product characteristics

| | |
|----------------------|--------|
| I _{F(AV)} | 3 A |
| V _{RRM} | 40 V |
| T _j (max) | 150° C |
| V _F (max) | 0.57 V |


Features and Benefits

- Very small conduction losses
- Negligible switching losses
- Low forward voltage drop
- Low thermal resistance
- Extremely fast switching
- Surface mounted device
- Avalanche capability specified

Description

Single chip Schottky rectifier suited for switch mode power supplies and high frequency DC to DC converters.

Packaged in DPAK, SMC, SMB, and low profile SMB, this device is intended for use in low and medium voltage operation, high frequency inverters, free wheeling and polarity protection applications where low switching losses are required.



Order codes

| Part Number | Marking |
|-------------|---------|
| STPS340U | U34 |
| STPS340S | S34 |
| STPS340B | S340 |
| STPS340B-TR | S340 |
| STPS340UF | FU34 |

1 Characteristics

Table 1. Absolute Ratings (limiting values)

| Symbol | Parameter | | Value | Unit |
|--------------|---|--|--------------|------|
| V_{RRM} | Repetitive peak reverse voltage | | 40 | V |
| $I_{F(RMS)}$ | RMS forward current | | DPAK | 6 |
| $I_{F(AV)}$ | Average forward current | $T_c = 135^\circ C \delta = 0.5$ | DPAK | A |
| | | $T_L = 105^\circ C \delta = 0.5$ | SMB/SMC | |
| | | $T_L = 115^\circ C \delta = 0.5$ | SMB flat | |
| I_{FSM} | Surge non repetitive forward current | $t_p = 10 \text{ ms sinusoidal}$ | 75 | A |
| P_{ARM} | Repetitive peak avalanche power | $t_p = 1 \mu\text{s} T_j = 25^\circ C$ | 1300 | W |
| T_{sig} | Storage temperature range | | -65 to + 150 | °C |
| T_j | Operating junction temperature ⁽¹⁾ | | 150 | °C |

1. $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$ condition to avoid thermal runaway for a diode on its own heatsink

Table 2. Thermal resistance

| Symbol | Parameter | | Value | Unit |
|---------------|------------------|----------|-------|------|
| $R_{th(j-l)}$ | Junction to lead | SMB | 25 | °C/W |
| | | SMB flat | 15 | |
| | | SMC | 20 | |
| $R_{th(j-c)}$ | Junction to case | | DPAK | 5.5 |
| | | | | °C/W |

Table 3. Static electrical characteristics

| Symbol | Parameter | Test Conditions | | Min. | Typ. | Max. | Unit |
|-------------|-------------------------|---------------------|-----------------|------|------|------|------|
| $I_R^{(1)}$ | Reverse leakage current | $T_j = 25^\circ C$ | $V_R = V_{RRM}$ | | | 20 | µA |
| | | $T_j = 125^\circ C$ | | | 2 | 10 | mA |
| $V_F^{(1)}$ | Forward voltage drop | $T_j = 25^\circ C$ | $I_F = 3 A$ | | | 0.63 | V |
| | | $T_j = 125^\circ C$ | | | 0.52 | 0.57 | |
| | | $T_j = 25^\circ C$ | $I_F = 6 A$ | | | 0.84 | |
| | | $T_j = 125^\circ C$ | | | 0.63 | 0.72 | |

1. Pulse test: $t_p = 380 \mu\text{s}, \delta < 2\%$

To evaluate the conduction losses use the following equation:

$$P = 0.42 \times I_{F(AV)} + 0.050 I_{F(RMS)}^2$$

Figure 1. Average forward power dissipation versus average forward current (per diode)




Figure 3. Average forward current versus ambient temperature ($\delta = 0.5$, per diode) (SMB flat)




Figure 5. Non repetitive surge peak forward current versus overload duration (maximum values) (SMB)




Figure 2. Average forward current versus ambient temperature ($\delta = 0.5$, per diode) (DPAK / SMB / SMC)




Figure 4. Non repetitive surge peak forward current versus overload duration (maximum values) (DPAK)




Figure 6. Non repetitive surge peak forward current versus overload duration (maximum values) (SMC)




Figure 7. Non repetitive surge peak forward current versus overload duration (maximum values) SMB flat




Figure 8. Normalized avalanche power derating versus pulse duration




Figure 9. Normalized avalanche power derating versus junction temperature




Figure 10. Relative variation of thermal impedance junction to ambient versus pulse duration (DPAK)




Figure 11. Relative variation of thermal impedance junction to ambient versus pulse duration (SMB)




Figure 12. Relative variation of thermal impedance junction to ambient versus pulse duration (SMC)




Figure 13. Relative variation of thermal impedance junction to lead versus pulse duration - SMB flat




Figure 15. Junction capacitance versus reverse voltage applied (typical values)




Figure 17. Thermal resistance junction to ambient versus copper surface under each lead (epoxy printed board FR4, $e_{CU} = 35 \mu m$) (DPAK)




Figure 14. Reverse leakage current versus reverse voltage applied (typical values)




Figure 16. Forward voltage drop versus forward current




Figure 18. Thermal resistance junction to ambient versus copper surface under each lead (epoxy printed board FR4, $e_{CU} = 35 \mu m$) (SMB / SMC)





Figure 19. Thermal resistance junction to ambient versus copper surface under each lead (epoxy printed board FR4, $e_{Cu} = 35 \mu m$) (SMB flat)




2 Package Information

- Band indicates cathode on SMB and SMC
- Epoxy meets UL94, V0

Table 4. DPAK dimensions

| Ref | Dimensions | | | |
|-----|-------------|-------|------------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 2.20 | 2.40 | 0.086 | 0.094 |
| A1 | 0.90 | 1.10 | 0.035 | 0.043 |
| A2 | 0.03 | 0.23 | 0.001 | 0.009 |
| B | 0.64 | 0.90 | 0.025 | 0.035 |
| B2 | 5.20 | 5.40 | 0.204 | 0.212 |
| C | 0.45 | 0.60 | 0.017 | 0.023 |
| C2 | 0.48 | 0.60 | 0.018 | 0.023 |
| D | 6.00 | 6.20 | 0.236 | 0.244 |
| E | 6.40 | 6.60 | 0.251 | 0.259 |
| G | 4.40 | 4.60 | 0.173 | 0.181 |
| H | 9.35 | 10.10 | 0.368 | 0.397 |
| L2 | 0.80 typ. | | 0.031 typ. | |
| L4 | 0.60 | 1.00 | 0.023 | 0.039 |
| V2 | 0° | 8° | 0° | 8° |

Figure 20. DPAK footprint dimensions (in millimeters)**Table 5. SMB dimensions**

| Ref. | Dimensions | | | |
|------|-------------|------|--------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A1 | 1.90 | 2.45 | 0.075 | 0.096 |
| A2 | 0.05 | 0.20 | 0.002 | 0.008 |
| b | 1.95 | 2.20 | 0.077 | 0.087 |
| c | 0.15 | 0.40 | 0.006 | 0.016 |
| E | 5.10 | 5.60 | 0.201 | 0.220 |
| E1 | 4.05 | 4.60 | 0.159 | 0.181 |
| D | 3.30 | 3.95 | 0.130 | 0.156 |
| L | 0.75 | 1.50 | 0.030 | 0.059 |


Figure 21. SMB footprint (dimensions in mm)

Table 6. SMB Flat dimensions

| Ref. | Dimensions | | | | | |
|------------------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 0.90 | | 1.10 | 0.035 | | 0.043 |
| b ⁽¹⁾ | 1.95 | | 2.20 | 0.077 | | 0.087 |
| c ⁽¹⁾ | 0.15 | | 0.40 | 0.006 | | 0.016 |
| D | 3.30 | | 3.95 | 0.130 | | 0.156 |
| E | 5.10 | | 5.60 | 0.200 | | 0.220 |
| E1 | 4.05 | | 4.60 | 0.189 | | 0.181 |
| L | 0.75 | | 1.50 | 0.029 | | 0.059 |
| L1 | | 0.40 | | | 0.016 | |
| L2 | | 0.60 | | | 0.024 | |

1. Applies to plated leads



Figure 22. SMB Flat footprint (dimensions in mm)

Table 7. SMC package mechanical data

| Ref | Dimensions | | | |
|-----|-------------|------|--------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A1 | 1.90 | 2.45 | 0.075 | 0.096 |
| A2 | 0.05 | 0.20 | 0.002 | 0.008 |
| b | 2.90 | 3.2 | 0.114 | 0.126 |
| c | 0.15 | 0.41 | 0.006 | 0.016 |
| E | 7.75 | 8.15 | 0.305 | 0.321 |
| E1 | 6.60 | 7.15 | 0.260 | 0.281 |
| E2 | 4.40 | 4.70 | 0.173 | 0.185 |
| D | 5.55 | 6.25 | 0.218 | 0.246 |
| L | 0.75 | 1.40 | 0.030 | 0.063 |

Figure 23. Foot print dimensions (in millimeters)

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com.

3 Ordering information

| Ordering type | Marking | Package | Weight | Base qty | Delivery mode |
|---------------|---------|----------|---------|----------|---------------|
| STPS340U | U34 | SMB | 0.107 g | 2500 | |
| STPS340S | S34 | SMC | 0.243 g | 2500 | Tape and reel |
| STPS340B | S340 | DPAK | 0.30 g | 75 | Tube |
| STPS340B-TR | | | | 2500 | Tape and reel |
| STPS340UF | FU34 | SMB flat | 0.50 g | 5000 | Tape and reel |

4 Revision history

| Date | Revision | Description of Changes |
|-------------|----------|---|
| Jul-2003 | 7B | Last update. |
| Feb-2005 | 8 | Layout update. No content change. |
| 08-Feb-2007 | 9 | Reformatted to current standard. Added ECOPACK statement. Added SMB flat package. |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com